



HDS 1000 Be

Independent of an external power supply: the heated HDS 1000 Be high-pressure cleaner with Honda petrol engine and electro start. Designed for demanding continuous use and suitable for crane loading.









1 Optimum ease of use

- Automatic burner cut-out in case of water shortage and overheating.
- The ergonomically designed spray gun reduces holding and pulling force.

2 Maximum performance

- High-output burner with upright heating coil and detonation-free continuous ignition.
- For removing stubborn encrustations.

TECHNICAL DATA AND EQUIPMENT





HDS 1000 Be

- Petrol engine with electro start
- Professional high-performance hot water machine

Technical data		
Order No.		1.811-942.0
EAN code		4054278169200
Pressure	bar / MPa	40-210 / 4-21
Pressure	PSI	3000
Flow rate	l/h	450-900
Max. temperature	°C	98 / 80
Heating oil or gas consumption, full load	kg/h	5.6
Motor type		GX 390/petrol
Engine manufacturer		Honda
Motor rating	kW / hp	9.5 / 13
Weight	kg	165
Dimensions (L × W × H)	mm	1100 × 750 × 785

Equipment		
Spray gun		EASY!Force Advanced
Spray gun with soft grip		
High-pressure hose	m	15
Spray lance	mm	1050
Cage frame		
Anti-twist system (AVS)		
Electro start		-
Power nozzle		
Servo Control		-
sturdy tubular steel frame for handling with crane	В	

■ Included in delivery.

























		Г	1	1				
		Order No.	ID	Max. working pressure	Length	Pr	rice	Description
Standard with unions on both sides	;							
High-pressure hose 2x EASY!Lock, ID 8, 315 bar, 10 m, ANTI!Twist	1	6.110-031.0	ID 8	315 bar	10 m			High-pressure hose (ID 8) suitable for up to 315 bar pressure. High-pressure hose with innovative EASY!Lock hand screw connection at both ends, ANTI!Twist, 10 m long.
High-pressure hose 2x EASY!Lock ID 8, 315 bar, 20 m, ANTI!Twist	2	6.110-032.0	ID 8	315 bar	20 m			High-pressure hose (ID 8), 20 m long, with time-saving and robust EASY!Lock hand screw connection at both ends. For up to 315 bar pressure.
High-pressure hose 2x EASY!Lock, ID 8, 315 bar, 30 m, ANTI!Twist	3	6.110-014.0	ID 8	315 bar	30 m			Convenient length (30 m) and innovative EASY!Lock hand screw connection: high-pressure hose (ID 8) with ANTI!Twist for up to 315 bar pressure.
High-pressure hose 2x EASY!Lock, ID 10, 220 bar, 15 m	4	6.110-042.0	ID 10	220 bar	15 m			With innovative EASY!Lock hand screw connection for up to 220 bar pressure: 15 m long high-pressure hose (ID 10).
High-pressure hose 2x EASY!Lock, ID 10, 220 bar, 20 m	5	6.110-043.0	ID 10	220 bar	20 m			Main features of this high-pressure hose (ID 10): 20 m long with extremely time-saving and convenient EASY!Lock hand screw connection at both ends.
High-pressure hose 2x EASY!Lock, ID 10, 220 bar, 25 m	6	6.110-044.0	ID 10	220 bar	25 m			Impressive values and basic equipment: high-pressure hose, (ID 10), 25 m long, for up to 220 bar pressure.
High-pressure hose 2x EASY!Lock, ID 12, 250 bar, 15 m	7	6.110-059.0	ID 12	210 bar	15 m			Suitable for up to 250 bar working pressure: high-pressure hose (ID 12), 15 m long, with convenient EASY!Lock hand screw connection at both ends.
High-pressure hose 2x EASY!Lock 2x EASY!Lock ID 12, 250 bar, 40 m	8	6.110-060.0	ID 12	210 bar	40 m			With EASY!Lock hand screw connection, 40 m long for wide working radius: high-pressure hose (ID 12) with EASY!Lock hand screw connection at both ends. Suitable for up to 250 bar working pressure.
High-pressure hose 2x EASY!Lock, ID 8, 315 bar, 15 m, ANTI!Twist	9	6.110-030.0	ID 8	315 bar	15 m			15 m long high-pressure hose, ID 8, with ANTI!Twist at both ends with time-saving EASY!Lock hand screw connection.
Longlife 400 with unions on both s	ides							
High-pressure hose Longlife 400 2x EASY!Lock, ID 8, 400 bar, 30 m, ANTI!Twist		6.110-023.0	ID 8	400 bar	30 m			Durable high-pressure hose with double steel reinforcement, ANT!!Twist and EASY!Lock hand screw connection at both ends. ID 8, 30 m long, for up to 400 bar pressure.
High-pressure hose Longlife 400 2x EASY!Lock, ID 8, 400 bar, 20 m, ANTI!Twist	11	6.110-027.0	ID 8	400 bar	20 m			High-pressure hose with ANT!!Twist, EASY!Lock hand screw connections and double steel reinforcement. 20 m long, ID 8, EASY!Lock hand screw connection at both ends.
High-pressure hose Longlife 400 2x EASY!Lock, ID 8, 400 bar, 15 m, ANTI!Twist	12	6.110-029.0	ID 8	400 bar	15 m			The double steel reinforcement ensures a long lifetime of this 15 m long high-pressure hose (ID 8), approved for up to 400 bar pressure hose.
High-pressure hose Longlife 400 2x EASY!Lock, ID 8, 400 bar, 1.5 m	13	6.110-024.0	ID 8	400 bar	1.5 m			1.5 m short high-pressure hose (ID 8). With convenient EASY!Lock hand screw connection at both ends for robust and fast connections. Durable, for up to 400 bar pressure.
High-pressure hose Longlife 400 1x EASY!Lock 1x M 22 x 1.5, ID 8, 400 bar, 1.5 m	14	6.110-069.0	ID 8	400 bar	1.5 m			High-pressure hose (ID 8) with double steel reinforcement, 30 m long, suitable for up to 400 bar pressure. Connectors: M 22 × 1.5, quick and convenient EASY!Lock hand screw connection.
High-pressure hose Longlife 400 2x EASY!Lock, ID 8, 400 bar, 10 m, ANT!!Twist	15	6.110-038.0	ID 8	400 bar	10 m			Durable, 10 m long high-pressure hose (ID 8) with double steel reinforcement and EASY!Lock hand screw connection at both ends and ANTI!Twist. Approved for 400 bar pressure.
Longlife food design with screw co	nnectio	ons at both ends						
High-pressure hose, food grade Longlife, 400 2x EASY!Lock, ID 8, 10 m, ANTI!Twist	16	6.110-053.0	ID 8	400 bar	10 m			With blue, non-marking and animal fat resistant outer covering: durable high-pressure hose (ID 8), 10 m long, AN-TI!Twist and EASY!Lock hand screw connection at both ends.





		Order No.	ID	Max. working pressure	Length	Price	Description
Special hoses							
High-pressure hose 1x EASY!Lock curved 1x M 22 x 1.5, ID 8, 400 bar, 1.5 m	17	6.110-068.0	ID 8	400 bar	1.5 m		For connection to hose reels: high-pressure hose, with M 22 × 1.5 connection and curved EASY!Lock hand screw connection. 1.5 m long, suitable for up to 400 bar working pressure.

[■] Included in delivery.

Available accessories.

Extension hose.











		Order No.	Flow rate			Price	Description
Trigger guns				<u> </u>			
EASY!Force Advanced	1	4.118-005.0					Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.
Servo control							
Servo Control controller with EASY!Lock	2	4.118-008.0	750-1100 l/h				-
Quick connect							
Quick coupling	3	2.115-000.0					For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 x 1.5 internal thread.
Male coupling	4	2.115-001.0					Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22 x 1.5 external thread.

[■] Included in delivery.

Available accessories.

Extension hose.





		Order No.	Nozzle size		Price	Description
Power nozzle spray angle 25°						
Powerduese TR fuer Ersatz 25047	1	2.113-009.0	47			Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.
HP nozzle spray angle 0°						
High-pressure nozzle with 0° spray angle	2	2.113-034.0	50			High-pressure nozzle with powerful jet for extremely stubborn dirt. $\hfill\Box$
Power nozzle spray angle 15°						
Power nozzle spray angle 15°	3	2.113-047.0	55			Fan jet nozzle with 15° spray angle suitable for stubborn dirt. $\hfill\Box$
Power nozzle spray angle 40°						
Power nozzle spray angle 40°	4	2.113-054.0	50			Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.

[■] Included in delivery.

Available accessories.

Extension hose.





			Max. working				
		Order No.	pressure	Length		Price	Description
Rotating spray lances		I.	_	I.			
1050 mm spray pipe, rotatable	1	4.112-000.0	300 bar	1050 mm			1050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.
Spray lance, 200 mm, rotatable	2	4.112-027.0	300 bar	250 mm			600 mm stainless steel lance (manual coupling) with ergo-
Spray lance, 400 mm, rotatable	3	4.112-024.0	300 bar	400 mm			nomic handle for ease of use and protection. Rotatable 360°
600 mm spray pipe, rotatable	4	4.112-007.0	300 bar	600 mm			under pressure.
850 mm spray pipe, rotatable	5	4.112-006.0	300 bar	840 mm			850 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.
1550 mm spray pipe, rotatable	6	4.112-018.0	300 bar	1550 mm			1550 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.
2050 mm spray pipe, rotatable	7	4.112-021.0	300 bar	2050 mm			2050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.
Double lance							
Double lance 960 mm	8	6.394-665.0	310 bar	960 mm			960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).
Angular spray lance		1	1	1			,
Spray lance for toilets and rain gutters	9	4.112-029.0					Stainless steel lance WC and gutter with nozzle insert. Spe- cially shaped for effective and hygienic cleaning of gutters and toilets.
Flexible spray lance							
Flexible lance 1050 mm	10	4.112-035.0	210 bar	1050 mm			1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.
Telescopic spray lance Telescopic spray lance	11	4.112-037.0	225 bar	5400 mm			Can be continuously extended from 1.8 to 5.4 m. For clean-
relescopic spray lance	11	4.112-037.0	223 041	3400 111111			ing areas that are difficult to reach, such as ceilings or fa- cades. With integrated HD trigger gun, M 22 x 1.5 connec- tion with rotary coupling. Connection for M 18 x 1.5 nozzles,
Strap for telescopic spray pipe	12	6.373-987.0					Convenient strap for relief when working with the telescopic spray lance (6.394-690). The burden is optimally distributed on the body and longer periods of use are possible.
Gutter cleaner							
Gutter cleaning lance	13	2.112-015.0					The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.
Undercarriage spray lance		1		1	,		,
Underbody lance	14	4.112-032.0		700 mm			Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.
Additional handle							
Additional handle for EASY!Lock spray lances	15	4.321-380.0					

spray lances

■ Included in delivery.

Available accessories.

Extension hose.





	Order No.					Price	Description
1	2.637-820.0						Practical kit with pneumatic tyres for HDS 1000 BE and HDS
							1000 DE high-pressure cleaners. For improved manoeuvra-
			L				bility.
2	4.111-024.0						l n
		1 2.637-820.0	1 2.637-820.0	1 2.637-820.0	1 2.637-820.0	1 2.637-820.0	1 2.637-820.0

[■] Included in delivery.

Available accessories.

Extension hose.





















	I	1			1		
		Order No.	Flow rate	Nozzle size	Diame- ter	Price	Description
Hard Surface Cleaner FRV 30							
Hose fastening attachment kit	1	2.642-528.0					
Dirt trap attachment kit	2	2.642-532.0					
FR 30 Me surface cleaner							
Hard Surface Cleaner FR 30 Me	3	2.111-013.0			300 mm		Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.
Hard Surface Cleaner FR 50							
Surface Cleaner FR 50 Me	4	2.111-023.0			500 mm		Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas.With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.
Machine-specific nozzle kits for FR							
Nozzle kit for surface cleaners	5	2.640-442.0	850-1100 l/h				Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (850 to 1100 l/h).
Machine-specific nozzle kits for FR	V						
Nozzle kit 050 - for FRV	6	2.642-433.0		50			
FRV 30 Me surface cleaner							
Extension hose FRV 30 Me and FRV 50 Me	7	4.441-040.0					
Surface Cleaner FRV 30 Me	8	2.111-012.0					
Surface Cleaner FR 50 Me							
Surface Cleaner FRV 50 ME	9	2.111-024.0					

[■] Included in delivery.

Available accessories.

Extension hose.































		Order No.			Price	Description	⊥
Nozzle union	1	L 4 4 4 2 0 4 4 0 L					Ţ
Protection part TR only for re- placement	1	4.112-011.0					[
Coupling parts				I			
Articulated joint	2	6.987-705.0				This articulated joint with variable angle adjustment (up to an angle of 120°) is recommended for cleaning hard to reac areas. Fits directly on the spray lance.	
Rotary coupling							
Rotary coupling	3	4.111-021.0				Reliably prevents twisting of HP hoses. Connection M 22 x 1.5 m. Handle protection	[
Coupling							Į,
Connector	4	4.111-037.0				For connecting and extending HP hoses, 2 x M 22 x 1.5 m connection, brass with rubber protection	[
Connector							
Screw sockets for surface cleaners and Servo Control controller	5	4.111-022.0				For attaching high-pressure nozzles and accessory parts to the HD trigger gun (with nozzle screws) - 1 x M 22 x 1.5/1 M 18 x 1.5.	
Short spray unit	6	4.111-038.0]
EASY!Lock adapter			1	I			
Adapter 1 M22 x 1.5 AG - EASY!Lock 22 AG	7	4.111-029.0				Adaptor for connecting pressure hoses with EASY!Lock and pressure hoses with M 22×1.5 connection.	L
Adapter 2 M22 x 1.5 IG - EASY!Lock 22 AG	8	4.111-030.0				Adaptor for connecting high-pressure cleaners or high-pres sure guns with M 22×1.5 connection and pressure hoses with EASY!Lock.	S- [
Adapter 3 M22 x 1.5 IG - EASY!Lock 22 AG	9	4.111-031.0				Adaptor for connecting high-pressure guns with M 22×1.5 connection and spray lances or Servo Control controllers with EASY!Lock.	
Adapter 4 EASY!Lock 22 IG - AVS	10	4.111-032.0				Adaptor for connecting pressure hoses with AVS swivel connection and EASY!Force high-pressure gun.	[
Adapter 5 EASY!Lock 22 IG - M22 x 1.5 AG	11	4.111-033.0				Adaptor for connecting EASY!Force high-pressure gun and spray lances with M 22 × 1.5 connection.	[
Adapter 6 EASY!Lock 22 IG - M22 x 1.5 AG	12	4.111-034.0				Adaptor for connecting pressure hoses with M 22×1.5 connection and EASY!Force high-pressure gun or high-pressure cleaners with EASY!Lock.	- [
Adapter 7 M18 x 1.5 IG - EASY!Lock 20 AG	13	4.111-035.0				Adaptor for connecting spray lances with M 18 × 1.5 connection and nozzles, surface cleaners or wash brushes with EASY!Lock.	-C- [
Adapter 8 EASY!Lock 20 IG - M18 x 1.5 AG	14	4.111-036.0				Adaptor for connecting nozzles, surface cleaners or wash brushes with M 18 × 1.5 connection and spray lances with EASY!Lock.	[
Cleaning agent injector							
Cleaning agent injector for high and low pressure (without nozzles)		4.637-032.0				Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	[
Cleaning agent injector for high pressure (without nozzle)	16	4.637-033.0				Cleaning agent dosage at high pressure 3 - 5 %	[
Machine-specific nozzle kit with or	der no	. 3.637-170.0					
Nozzle kit 750-1000 l/h	17	4.769-047.0				For HD/HDS 750 - 1000 l/h. Consists of nozzle insert + HP power nozzle + union	[
Nozzle insert with order no. 3.637-	001.0						Ċ
Nozzle insert up to 1,100 l/h - high pressure	18	4.769-003.0				Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	1





		Order No.			Price	Description	
Nozzle insert up to 1,100 l/h - low	19	4.769-001.0				For low pressure with machines up to 1.100 l/h	
pressure							

[■] Included in delivery.

Available accessories.

Extension hose.







		ı		T					\neg
		Order No.	Nozzle size				Price	Description	
Wet blasting attachment (without n	ozzle)		•	'	'	'			
Wet blasting attachment with flow control (without nozzles)	1	4.115-000.0						Paint, rust and scale removal made easy: Kärcher wet blast- ing attachment with flow control for adding blasting abra- sive to the high-pressure jet.	
Wet blasting attachment without flow control (nozzles not included)	2	4.115-006.0						Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.	
Nozzle kits for wet jet unit									
Nozzle pack TR wet jet set 0050	3	2.112-023.0	50					Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment .	
Boron carbide nozzle									
Boron carbide nozzle, for ma- chines up to 1,000 l/h	4	6.415-084.0	6 mm					In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	

[■] Included in delivery.

Available accessories.

Extension hose.











		I					I	$\overline{}$	
		Order No.	Max. working pressure	Nozzle size	Diame- ter	Price	Description		
Pipe cleaning hose, ID 6		<u>'</u>	·						
Pipe cleaning hose, ID 6, 10 m, max. 250 bar	1	6.110-046.0	250 bar				The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	r 🗆	
Pipe cleaning hose, ID 6, 20 m, max. 250 bar	2	6.110-008.0	250 bar				The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	r 🗆	
Pipe cleaning hose, ID 6, 30 m, max. 250 bar	3	6.110-047.0	250 bar				The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	r 🗆	
Pipe cleaning nozzle									
Pipe cleaning dirt blaster D 25 / 060	4	6.415-945.0		60	25 mm		The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the		
Pipe cleaning dirt blaster D 30 / 060	5	6.415-947.0		60	30 mm		necessary forward movement, as well as convenient handling.		
Pipe cleaning dirt blaster D 35 / 060	6	6.415-949.0		60	35 mm				
Pipe cleaning nozzle	7	5.763-015.0		55	16 mm		16 mm pipe cleaning nozzle with internal thread. Various jet	t 🗆	
	8	5.763-016.0		60	16 mm		directions for environmentally-friendly cleaning of blocked drains and pipes.		
	9	5.763-017.0		50	30 mm		Pipe cleaning nozzle with inner thread. Different spray directions. The hose moves freely through the pipe. (R 1/8" connection, 3 x 30° backwards, diameter 30 mm.)		
Rotating pipe cleaning nozzle	10	6.415-428.0		50	16 mm		Pipe cleaning nozzle with four rotating jets and inner thread. Different spray directions. The hose moves freely through the pipe. With R 1/8" connection.		

[■] Included in delivery.

Available accessories.

Extension hose.





		Order No.	Max. working pressure	Nozzle size		Price	Description	
Dirt blaster, large								
Dirt blaster	1	4.114-027.0	300 bar	50			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	

 $[\]blacksquare$ Included in delivery. \qed Available accessories. $\ \, \blacktriangle$ Extension hose.

















			I				
		Order No.	Flow rate			Price	Description
Cup foam lance		ı	I	ı	I.		
Cup foam lance Advanced 025	1	2.112-017.0					Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design.
1-litre cleaning agent container for foam lance	2	6.414-954.0					
Inno Foam Kit							
Inno Foam Set with detergent injector	3	2.112-000.0					High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and
Inno Foam Set	4	2.112-008.0					stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.
Easy Foam Set							
Easy Foam Set with RM injector	5	2.112-010.0					HP foam system for use with. HD/HDS units for cleaning and
Easy Foam Set	6	2.112-011.0					disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.
Nozzle kits for Inno/Easy Foam Set							
Nozzle kit 090 for Inno / Easy Set 700-1,000 l/h	7	2.111-019.0	700-1000 l/h				Nozzle kit contains Kärcher power nozzles and nozzle inserts. For Inno/Easy-Foam set 700-1000 I/h. For optimal foam system performance.
Foam nozzle mounting kit							
Foam nozzle attachment kit	8	2.112-013.0					Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.

[■] Included in delivery.

Available accessories.

Extension hose.



















Manual haranta (Manharata)		Order No.	Length		Price	Description	
Manual hose reel attachment kit Hose reel attachment kit for HDS petrol machines	1	2.110-005.0	20 m			Hose reel attachment kit for installation on the machine. For safe and tidy storage of high-pressure hoses (with connection hose to machine HP outlet). Rotatable under pressure with connection 22 x 1.5.	
Automatic, self-winding hose reels Automatic hose reel, powder-coat- ed steel / plastic	2	6.392-074.0	20 m			Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	
Automatic stainless steel / syn- thetic material hose drum	3	6.392-083.0	20 m			Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	
Automatic hose reel, coated	4	6.392-106.0	20 m			Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	
Add-on kit hose reel lacquered basaltgra	5	6.392-105.0	20 m				
Automatic hose reel, stainless steel, includes swivel holder	6	6.392-076.0	20 m			Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	
ABS automatic stainless steel hose drum	7	6.392-122.0	20 m			High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrossion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.	
Powder-coated swivel holder	8	2.639-931.0				Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	
Pivoting stainless steel wall brack- et attachment kit	9	2.641-867.0				Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	

[■] Included in delivery.

Available accessories.

Extension hose.











		Order No.	Flow rate	Inlet tempera- ture	Length	Length	Price	Description
Solar cleaning - telescopic lances								
iSolar TL 14 C (without hose)	1	4.110-002.0		max. 60 °C				Full carbon telescopic rod for maximum rigidity with minimal weight. With 14 m max. reach and practical quick-release couplings for easy extension and retraction.
iSolar TL 10 C (without hose)	2	4.110-007.0		max. 60 °C				
iSolar TL 10 H (without hose)	3	4.110-003.0		max. 60 °C				Telescopic rod made from a carbon/fibreglass mixture for maximum rigidity with minimum weight. With 10 m max. reach and practical quick-release couplings for easy extension and retraction.
iSolar TL 7 H (without hose)	4	4.110-004.0		max. 60 °C				Telescopic rod made from a carbon/fibreglass mixture for maximum rigidity with minimum weight. With 7.2 m max. reach and practical quick-release couplings for easy extension and retraction.
iSolar HP hose 7	5	6.392-978.0		max. 155 °C				High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.
iSolar HP hose 10	6	6.392-977.0		max. 155 °C				High-quality, flexible HP hose (with rubber covering) for the isolar TL 10. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.
iSolar HP hose 14	7	6.392-976.0		max. 155 °C				High-quality, flexible HP hose (with rubber covering) for the isolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.

[■] Included in delivery. □ Available accessories. ▲ Extension hose.









		Order No.	Flow rate		Price	Description
Push-on washing brush						
Push-on wash brush	1	4.113-001.0				For general-purpose cleaning of all surfaces. Clamps directly onto the spray lance. Connection M 18×1.5
Rotating washing brush						
Rotating wash brush for > 800 l/h machines, nylon bristles	2	4.113-002.0	800-1300 l/h			Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to
Rotating wash brush for > 800 l/h machines, natural bristles	3	4.113-005.0	800-1300 l/h			60°C, M 18 x 1.5 (replaceable brush insert).

[■] Included in delivery.

Available accessories.

Extension hose.















		Г	1					
		Order No.	Length	Diameter		Price	Description	
Geka coupling								
Geka connector with hose barb, R _1"	1	6.388-465.0						
Geka connector with internal thread, R 1"	2	6.388-458.0					with female thread	
Suction filter								
Water suction filter	3	6.414-956.0						
Suction filter with check valve	4	4.730-012.0					Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	
Water fine filter								
Water fine filter, 90-120 μ m, R 1", suitable for pressure and vacuuming operation	5	2.638-255.0					Mounts to machine, suitable for pressure and suction mode, 90-120 μm	
Water fine filter, with adapter	6	4.730-102.0					Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	
Water fine filter, 100 µm, R 1"	7	2.638-270.0					Fine-mesh water filter, 100 µm, max. temperature 60°C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connector 1".	

[■] Included in delivery.

Available accessories.

Extension hose.